## CLAIMS

- 1. Method for the separation of particles (40, 42) with different sizes, immersed in a liquid, this method including:
  - introduction of radiation (30) in a waveguide (20), coupled to a second guide in a coupling area, this radiation entraining all particles towards the coupling area,
  - separation of the particles as they pass into the coupling area.

10

5

- 2. Method according to claim 1, the distance between the two guides in the coupling area being less than 5  $\mu m\,.$
- $_{15}$   $_{\,\,\,}$  3. Method according to either claim 1 or 2, the length of the coupling area being between 10  $\mu m$  and 50  $\mu m$  .
- 4. Method according to one of claims 1 to 20 3, the particles being cells or macromolecules or microballs.
- 5. Method according to one of claims 1 to 4, the injected radiation being in a spectral range 25 between the near ultraviolet and the infrared.
  - 6. Method according to one of claims 1 to 3, the particles being microballs, and microball marked cells, and the radiation being in the infrared range.

WO 2005/054818 PCT/EP2004/053261

17

7. Method according to one of claims 1 to 6, the diameter of the particles being between firstly 100 nm and 500 nm, and secondly between 600 nm and 1.5  $\mu$ m or between 1  $\mu$ m and 100  $\mu$ m.

5

Arrige L

- 8. Method according to one of claims 1 to 7, the liquid in which the particles are immersed being water or a cell suspension medium.
- 9. Method according to one of claims 1 to 8, some particles being metallic or being marked by metallic particles.
- 10. Method according to claim 9, some 15 particles being gold particles or being marked by gold particles.
- 11. Method according to one of claims 1 to 10, the radiation injected in the waveguide being 20 polarised in transverse magnetic mode.
- 12. Particle separation device, comprising two optical guides (20, 22) coupled by a coupling area with a length between 10  $\mu$ m and 50  $\mu$ m, the distance between the guides being less than 5  $\mu$ m.
- 13. Device according to claim 12, also comprising means (162) of sending radiation with a wavelength of between 300 nm and 1.2  $\mu$ m or even 1  $\mu$ m 30 and 1.2  $\mu$ m in one of these guides.

14. Device according to either claim 12 or 13, also comprising means (162) of sending radiation polarised in transverse magnetic mode in one of these guides.

5

15. Device according to one of claims 12 to 14, also comprising means (160, 170) of displaying separation of particles.